

08-18-00

A

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

ATTY DOCKET NO.: 9209-3

DATE: August 17, 2000

**UTILITY PATENT APPLICATION TRANSMITTAL LETTER
AND FEE TRANSMITTAL FORM (37 CFR 1.53(b))**

BOX PATENT APPLICATION

Assistant Commissioner for Patents

Washington, DC 20231

Sir:

Transmitted herewith for filing under 37 CFR 1.53(b) is:

- ☒ a patent application
☐ a Continuation ☐ a Divisional ☐ a Continuation-in-Part (CIP)
of prior application no.: ; filed .
☐ A Small Entity Statement(s) was filed in the prior application; Status still proper and desired.

Inventor(s) or Application Identifier:

KENNETH LEE HARPER

Entitled: **METHODS, SYSTEMS AND COMPUTER PROGRAM PRODUCTS FOR
DETERMINING A POINT OF LOSS OF DATA ON A COMMUNICATION NETWORK**

Enclosed are:

1. ☒ Application Transmittal Letter and Fee Transmittal Form (*A duplicate is enclosed for fee processing*)
2. ☒ 45 pages of Specification (including 49 claims)
3. ☒ 7 sheets of Formal Drawings (35 USC 113)
4. ☒ Oath or Declaration
 - a. ☒ newly executed (*original or copy*)
 - b. ☐ copy from prior application (37 CFR 1.63(d) (*for continuation/divisional*) [Note Box 5 Below]
 - c. ☐ DELETION OF INVENTOR(S) (*Signed statement deleting inventor(s) named in the prior application*)
5. ☐ Incorporation By Reference (*useable if box 4b is checked*)

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (*Appendix*)
7. ☒ Assignment papers (*cover sheet(s) and document(s)*)
8. ☒ Small Entity Statement(s)
9. ☐ Information Disclosure Statement, PTO-1449, and references cited
10. ☐ Preliminary Amendment (*Please enter all claim amendments prior to calculating the filing fee.*)
11. ☐ English Translation Document
12. ☐ Certified Copy of

13. ☐ Sequence Listing/ Sequence Listing Diskette
 a. ☐ computer readable copy
 b. ☐ paper copy
 c. ☐ statement in support
 14. ☐ An Associate Power of Attorney
 15. ☒ Return Receipt Postcard (MPEP 503) *(Should be specifically itemized)*
 16. ☐ Other:

The fee has been calculated as shown below:

	Column 1 No. Filed	Column 2 No. Extra	Small Entity Rate Fee	Large Entity Rate Fee
BASIC FEE			\$345.00	\$690.00
TOTAL CLAIMS	45 - 20 =	25	x 09 = \$225.00	x 18 = \$
INDEP CLAIMS	4 - 3 =	1	x 39 = \$ 39.00	x 78 = \$
<input type="checkbox"/> MULTIPLE Dependent Claims Presented			+ 130 = \$	+ 260 = \$
<i>If the difference in Col. 1 is less than zero, Enter "0" in Col. 2</i>			Total \$ 609.00	Total \$

- ☒ A check in the amount of \$ to cover the filing fee is enclosed.
- ☒ A check in the amount of \$649.00 is enclosed to cover the filing fee, PLUS the Assignment Recordation fee (\$40.00).
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 50-0220.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.

Respectfully submitted,



Robert W. Glatz
 Registration No. 36,811


Correspondence Address:
 USPTO Customer Number: **20792**
 Myers Bigel Sibley & Sajovec
 Post Office Box 37428
 Raleigh, North Carolina 27627
 Telephone (919) 854-1400
 Facsimile (919) 854-1401

CERTIFICATE OF EXPRESS MAILING

Express Mail Label No. EL533613821US
 Date of Deposit: August 17, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to Box Patent Application, Assistant Commissioner For Patents, Washington,

DC 20231


 Michele P. McMahan

Date of Signature: August 17, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney's Docket No. 9209-3

Applicant: Kenneth Lee Harper

Serial No.: To be assigned

Filed: Concurrently herewith

Title: **METHODS, SYSTEMS AND COMPUTER PROGRAM PRODUCTS
FOR DETERMINING A POINT OF LOSS OF DATA ON A
COMMUNICATION NETWORK,**

VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS
(37 C.F.R. § 1.9(f) & 1.27(c))--SMALL BUSINESS CONCERN

I hereby declare that I am

☐
☒

the owner of the small business concern identified below:
an official of the small business concern empowered to act
on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN: Trendium, Inc.
ADDRESS OF SMALL BUSINESS CONCERN: 55 Weston Road, Suite 402
Fort Lauderdale, Florida 33326

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 C.F.R. § 121.1301-1305, and reproduced in 37 C.F.R. § 1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time, or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

☒
☐
☐

the specification filed herewith with title as listed above.
the application identified above.
the patent identified above.

If the rights held by the above-identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate verified statements averring to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent

inventor under 37 C.F.R. 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 C.F.R. § 1.9(d), or a nonprofit organization under 37 C.F.R. § 1.9(e).

Each person, concern, or organization having any rights in the invention is listed below:

- ☒ no such person, concern, or organization exists.
☐ each such person, concern, or organization is listed below.

Name: _____

Address: _____
☐ Individual ☐ Small Business ☐ Nonprofit Organization

Name: _____

Address: _____
☐ Individual ☐ Small Business ☐ Nonprofit Organization

Separate verified statements are required from each named person, concern, or organization having rights to the invention averring to their status as small entities. (37 C.F.R. § 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 C.F.R. § 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING: Hanafy Meleis

TITLE OF PERSON OTHER THAN OWNER: President & Chief Executive Officer

ADDRESS OF PERSON SIGNING: 55 Weston Road, Suite 402, Fort Lauderdale, FL 33326

SIGNATURE:  DATE: 8/16/2000

METHODS, SYSTEMS AND COMPUTER PROGRAM PRODUCTS FOR
DETERMINING A POINT OF LOSS OF DATA ON A COMMUNICATION
NETWORK

Field of the Invention

The present invention relates to network communications and, more particularly, to analysis of network communication paths.

5

Background of the Invention

Computer networks have grown increasingly complex with the use of distributed client/server applications, mixed platforms and multiple protocols all in a single physical backbone. The control of traffic on networks is likewise moving from centralized information systems departments to distributed work groups. The growing utilization of computer networks is not only causing a move to new, high speed technologies, but is at the same time making the operation of computer networks more critical to day to day business operations. The use of quality of service (QoS) criteria for managing and/or contracting communication service level agreements (SLAs) is becoming increasingly common in networks, such as networks supporting Internet protocol (IP) communications.

10

15

Deregulation of telecommunications providers, new communications technologies, and the Internet have often been cited as important factors in bringing

about increased competition in the delivery of telecommunications services. As a result of this increased competition, telecommunications providers have generally been under pressure to improve efficiency and cut costs and yet still maintain a high quality level of service for their customers. In this competitive environment, one area
5 in which telecommunications providers may be able to gain a competitive edge is in the support systems that are used to operate, manage, and maintain the telecommunications networks. These support systems may be called operational support systems (OSS).

Broadly stated, an OSS for a telecommunications network may include
10 software services that are used to support the operations of a telecommunications network. Three support areas that may be addressed by a telecommunications OSS are 1) provisioning and order management, 2) billing and customer support, and 3) network management. Provisioning and order management may include such functions as service activation, service order processing, and service provisioning.
15 Billing and customer support may include such functions as data collection, retail and wholesale billing, bill compilation, and customer care. Finally, network management and/or network service quality management may include such functions as fault management, performance monitoring, error analysis, and security.

One problem related to network management which may be encountered is a
20 loss of data records during transmission from a source device to a destination device over a communication network. It is desirable, under such circumstances, to be able to identify the root cause device for such lost data records, so as, for example, to facilitate prompt initiation of corrective actions. However, the increasingly complex structure of such communications networks, such as the Internet, complicates the
25 identification of the root cause for such losses given the numerous routing devices which may define the network between the source and destination device and further given the nature of the structure of the Internet in which it is common to have a variety of different paths which may be utilized for transmission of data records between a given source and destination device. It is known with various
30 commercially available network management system packages to utilize commands such as segment path identification commands and "ping" features in combination

with direct queries to the routing devices defining the topology of a network to obtain status and performance information. This approach generally relies on overall performance information from the various routing devices defining the communications network based on either passive or active generated data transmissions to characterize the status of communications network components rather than evaluating the specific data flow which encountered the lost data records and directly identifying a point of loss.

Summary of the Invention

Embodiments of the present invention include methods, systems and computer program products for determining a point of loss for data records to be communicated between a source and a destination on a communication network. A topology of the communication network between the source and the destination is determined which includes a plurality of connecting nodes. A number of data records from the source directed to the destination passing between ones of the connecting nodes during a determined period of time is monitored. At least one of the connecting nodes is identified as the point of loss based on the monitored number of data records and the determined topology.

In further embodiments of the present invention, a plurality of network appliances configured to obtain a number of data records passing between a pair of connecting nodes during a time period are positioned between respective ones of the connecting nodes. Monitoring operations utilize the network appliances by identifying at least one of the network appliances on the topology and obtaining the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time.

Operations in accordance with embodiments of the present invention may include identifying at least one first hop one of the network appliances which is coupled to the source over the communication network. In addition, at least one next hop one of the network appliances is identified which is coupled between the at least one first hop one of the network appliances and the destination. A number of data records from the source directed to the destination obtained by the at least one first

hop one of the network appliances and the at least one next hop one of the network appliances during the determined time period is obtained. The number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances is compared with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination. A connecting node positioned between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances is identified as the point of loss for data records if the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination. The first hop network appliance may be coupled to the source without intervening ones of the network appliances. The next hop network appliance(s) may be coupled between the first hop network appliance and the destination without intervening ones of the network appliances.

In yet other embodiments of the present invention, a number of data records from the source directed to the destination obtained by an upstream one of the network appliances is compared with a number of data records from the source directed to the destination obtained by at least one downstream one of the network appliances coupled between the upstream one of the network appliances and the destination at an adjacent downstream position. Comparisons are performed for successive ones of the network appliances until either the destination is reached or at least one of the connecting nodes is identified as the point of loss for data. A connecting node positioned between the upstream one of the network appliances and corresponding downstream ones of the network appliances is identified as the point of loss for data records if the number of data records from the source directed to the destination obtained by the upstream one of the network appliances differs by a threshold amount from the number of data records from the source directed to the

destination obtained by the corresponding downstream ones of the network appliances. Comparison operations may further be repeated for successive ones of the network appliances on the topology until the destination is reached even after a point of loss is identified and all connecting nodes positioned between upstream ones of the network appliances and corresponding downstream ones of the network appliances may be identified as points of loss for data records if the number of data records from the source directed to the destination obtained by respective upstream ones of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by corresponding downstream ones of the network appliances.

In further embodiments of the present invention, the obtained numbers of data records from the source directed to the destination are adjusted to compensate for in transit introduced changes to data records before comparing the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination. The obtained numbers of data records from the source directed to the destination may be adjusted to compensate for encryption related changes in data records introduced by a connecting node coupled between the a first hop one and at least one next hop one of the network appliances.

In other embodiments of the present invention, the determined period of time is defined for the at least one first hop one of the network appliances and the at least next hop one of the network appliances based on a delay between the at least one first hop one of the network appliances and the at least next hop one of the network appliances. The determined time period may be defined for the at least one first hop one of the network appliances and the at least next hop one of the network appliances based on an average delay between the at least one first hop one of the network appliances and the at least next hop one of the network appliances determined over an averaging window.

In further embodiments of the present invention, the threshold amount is

defined based on an expected timing related variability between numbers of data records obtained by ones of the network appliances. The threshold amount may be defined based on a percentage of data record throughput for respective ones of the network appliances.

5 In yet other embodiments of the present invention, the connecting nodes are routing devices selected from the group consisting of routers, bridges and switches. A network appliance may be positioned between each defined connecting node in the topology and all other adjacent defined connecting nodes in the topology. One or more of the defined connecting nodes may include a plurality of routing devices.

10 In further embodiments of the present invention, systems are provided for determining a point of loss for data records to be communicated between a source and a destination on a communication network. The system includes a memory including a topology of the communication network between the source and the destination, the topology including a plurality of connecting nodes. A receiver receives from a
15 plurality of network appliances at determined locations on the communication network a number of data records from the source directed to the destination passing between ones of the connecting nodes during a determined period of time. A comparison circuit identifies at least one of the connecting nodes as the point of loss based on the received number of data records, the locations of the network appliances
20 and the topology.

 The systems in further embodiments include the plurality of network appliances. Pairs of the connecting nodes define segments of the topology between the source and the destination. At least one of the network appliances is coupled between each of the pairs of the connecting nodes. The network appliances in further
25 embodiments include a timer. A filter identifies ones of a plurality of data records detected by the at least one of the network appliances that are being transmitted from the source to the destination on the communications network. A counter counts filtered ones of the plurality of data records, the counter being configured to be reset responsive to the timer. A transmitter transmits counts from the counter to the
30 receiver. The filter may be configured to identify ones of the plurality of data records based on the source Internet Protocol (IP) address and destination IP address of a data

packet containing data records detected by the at least one of the network appliances.

While the invention has been described above primarily with respect to method aspects of the invention, both systems and/or computer program products are also provided.

5

Brief Description of the Drawings

Figure 1 is a block diagram of a network of data processing systems connected over a communications network and including a service quality management station (SQMS) and network appliances according to embodiments of the present invention;

10

Figure 2 is a block diagram of a data processing system suitable for use as a service quality management station or a network appliance in embodiments of the present invention;

Figure 3 is a more detailed block diagram of data processing systems providing a service quality management station according to embodiments of the present invention;

15

Figure 4 is a block diagram of a network appliance according to embodiments of the present invention;

Figure 5 is a schematic block diagram of a network topology between a source and a destination including network appliances according to embodiments of the present invention;

20

Figure 6 is a flowchart illustrating operations for determining a point of loss for data records according to embodiments of the present invention; and

Figure 7 is a flowchart illustrating operations for determining a point of loss for data records according to further embodiments of the present invention.

25

Detailed Description of Preferred Embodiments

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein;

30

rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

As will be appreciated by one of skill in the art, the present invention may be embodied as a method, data processing system, or computer program product.

- 5 Accordingly, the present invention may take the form of an entirely software embodiment or an embodiment combining software and hardware aspects. Furthermore, the present invention may take the form of a computer program product on a computer-usable storage medium having computer-usable program code embodied in the medium. Any suitable computer readable medium may be utilized
- 10 including hard disks, CD-ROMs, optical storage devices, or magnetic storage devices.

- Computer program code for carrying out operations of the present invention may be written in an object oriented programming language such as Java®, Smalltalk or C++. However, the computer program code for carrying out operations of the present invention may also be written in conventional procedural programming
- 15 languages, such as the "C" programming language. The program code may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer. In the latter scenario, the remote computer may be connected to the user's computer through a local area network (LAN) or a wide area
- 20 network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

- The present invention is described below with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the invention. It will be understood
- 25 that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the
- 30 instructions, which execute via the processor of the computer or other programmable

data processing apparatus, create means for implementing the functions specified in the flowchart and/or block diagram block or blocks.

These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including instruction means which implement the function specified in the flowchart and/or block diagram block or blocks.

The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions specified in the flowchart and/or block diagram block or blocks.

Various embodiments of the present invention will now be described with reference to **Figures 1** through **7**. **Figure 1** is a block diagram of a computer network including a service quality management station (SQMS) **150** supporting evaluation of loss of data records between a source one and a destination one of the servers **105**, **108** and the client **145**. As illustrated in **Figure 1**, the communication network **100** includes a plurality of connecting nodes and endpoint nodes. The server **105** and the server **108** as well as the SQMS **150** and the client **145** are shown as endpoint nodes in **Figure 1**. However, it is to be understood that each of these devices may also operate as a connecting node to other devices on the communication network **100**.

Both the server **105** and the server **108** connect through a network appliance **115** to a routing device **120**. The routing device **120** may be a router, a bridge, a switch, etc. As used herein, the terms bridge and switch will be used interchangeably and may be referred to as "bridge/switch" as such devices will be understood by those of skill in the art to be essentially interchangeable for purposes of the present invention. A bridge/switch as used herein may best be understood by contrast to a router. In particular, a bridge/switch, as contrasted with a router, does not use layer three protocol information, for example, Internet Protocol (IP) information, to process

communications from devices passing through the bridge/switch. They are otherwise interchangeable with routers for purposes of the present invention and bridge/switches and routers all generally be referred to as routing devices. An example of a network appliance suitable for use with the present invention in that it may provide

5 information related to data counts passing between nodes for particular source and destination devices is the QoSWorks™ product available from Sitara Networks of Waltham, Massachusetts.

The routing device **120** illustrated in **Figure 1** connects to the IP network **125**. The IP network **125** is further connected to the router **120'**. The IP network **125** is
10 illustrated schematically as a cloud and may include one or more additional routing devices and/or network appliances along the network's path between the router **120** and the router **120'**.

Operations of the SQMS **150** and the network appliances **115** will be further described herein with reference to the flowchart illustrations and block diagrams. It is
15 to be understood, however, that the communication network **100** may be provided by wired or wireless links using a variety of physical layer media and still stay within the teachings and scope of the present invention. Furthermore, while the network appliances **115** are illustrated as separate from the routing devices **120**, **120'** in **Figure 1** (see also, **Figure 5**), they may be implemented as operative aspects of the routing
20 devices **120**, **120'** while still falling within the scope of the present invention. Also, while the communication network **100** is illustrated as a computer network, it may be a variety of types of communication network such as voice, video and/or data including a variety of source/destination node devices defining the communication network.

25 An exemplary embodiment of a data processing system **230** suitable for use to determine a point of loss for data records in accordance with embodiments of the present invention is illustrated in **Figure 2** and typically includes input device(s) **232** such as a keyboard or keypad, a display **234**, and a memory **236** that communicate with a processor **238**. The data processing system **230** may further include a speaker
30 **244**, and an I/O data port(s) **246** that also communicate with the processor **230**. The I/O data port(2) **246** can be used to transfer information between the data processing

system **230** and another computer system or a network (*e.g.*, the Internet) such as the communication network **100**. The communication network **100** need not be an Internet Protocol network but may be a variety of known communication protocol based networks. These components may be conventional components such as those
5 used in many conventional data processing systems which may be configured in accordance with the present invention to operate as described herein. The present invention may be utilized with any data processing systems which are capable of carrying out the operations of embodiments of the present invention described herein. The data processing system **230** may be configured as a SQMS **150** and/or a network
10 appliance **115**.

Figure 3 is a block diagram of a data processing system that illustrates systems, methods, and computer program products in accordance with embodiments of the present invention. The processor **238** communicates with the memory **236** via an address/data bus **237**. The processor **238** can be a variety of commercially
15 available or custom microprocessors. The memory **236** is representative of the overall hierarchy of memory devices containing the software and data used to implement the functionality of the data processing system **230**. The memory **236** can include, but is not limited to, the following types of devices: cache, ROM, PROM, EPROM, EEPROM, flash, SRAM, and DRAM.

As shown in **Figure 3**, the memory **236** may contain several categories of software and data used in the data processing system **230**: the operating system **320**; the application programs **340**, the input/output (I/O) device drivers **315**; and the data **310**. As will be appreciated by those of skill in the art, in certain embodiments of the present invention, the operating system **320** may be a variety of operating systems
25 suitable for use with a data processing system, such as OS/2, AIX or OS/390 from International Business Machines Corporation, Armonk, NY, WindowsCE, WindowsNT, Windows95, Windows98 or Windows2000 from Microsoft Corporation, Redmond, WA, PalmOS from Palm, Inc., MacOS from Apple Computer, UNIX or Linux, proprietary operating systems or dedicated operating
30 systems, for example, for embedded data processing systems.

The I/O device drivers **315** typically include software routines accessed through the operating system **320** by the application programs **340** to communicate with devices such as the input devices **232**, the display **234**, the speaker **244**, the I/O data port(s) **246**, and certain components of the memory **236**. The application
5 programs **340** are illustrative of the programs that implement the various features of the data processing system **230**. The data **310** represents the static and dynamic data used by the application programs **340**, the operating system **320**, the I/O device drivers **315**, and other software programs that may reside in the memory **236**.

For the embodiments illustrated in **Figure 3** of the present invention, a
10 topology detection circuit **350** is included which obtains the necessary information to identify the connecting nodes and paths between a source device and a destination device. This information may be provided, for example, by the topology data **345** which may include a topology definition for the communication network between the source and the destination which includes the connecting nodes between the two
15 destinations defining the possible different paths data records could travel when being transmitted from the source to the destination. Alternatively, as will be understood by those of ordinary skill in the art, topology information can be initially obtained and/or updated by active communications between a service quality management station and routing devices included in the communications network which, typically, retain
20 information describing source and destination devices connected to ports of the respective routing devices, for example, by tracking the IP address information for incoming and outgoing packets. However, the benefits of the present invention may be realized utilizing such topology information regardless of how it is obtained or updated and, accordingly, the invention is not to be limited by the source of the
25 topology information.

As shown for the embodiments of **Figure 3**, the present invention in various aspects further provides a receive circuit **355** or other receiver device that receives from a plurality of network appliances which are located at determined locations on the communication network, a number of data records originated from a source device
30 and directed to a destination device which pass between ones of the connecting nodes during a determined time period. A comparison circuit **330** identifies one or more of

the connecting nodes as a point of loss based on the received number of data records from the receive circuit 355 and the known information regarding the locations of the network appliances providing counts for numbers of data records received and the topology information defining the communication network.

5 While the present invention is illustrated, for example, with reference to the comparison circuit 330 being a separate program, as will be appreciated by those of skill in the art, the comparison circuit 330 (as well as the topology detection circuit 350 and the receive circuit 355) may also be incorporated into the operating system 320 or the I/O device drivers 315. Thus, the present invention should not be
10 construed as limited to the configuration of **Figure 3** but is intended to encompass any configuration capable of carrying out the operations described herein.

Referring now to **Figure 4**, a network appliance device 400 in accordance with embodiments of the present invention will now be further described. The network appliance 400 is connected to a service quality management station 410, such as the
15 system described with reference to **Figure 3**, over the IP network 405. As shown in **Figure 4**, an additional network device 412, which may be the source or the destination for various monitored data record flows, is also connected through the IP network 405. However, it is to be understood that the communication connection between the service quality management station 410 and a network appliance 400
20 need not be over a common network used by the network appliance 400 to detect data record flows to and from devices such as the network device 412.

The network device 412 may, for example, be a computer device operating as a server, such as the endpoint servers 105 and 108 illustrated in **Figure 1**, or a client device such as the client 145 illustrated in **Figure 1**. Furthermore, as noted previously
25 in the connection with the description of **Figure 1**, the server 105, the server 108 or the client 145 may operate as either a source or a destination device under various circumstances.

There will typically be a plurality of network devices 412 which are monitored as well as a plurality of network appliances 400 connected between routing devices
30 defining connecting nodes on the communications network. Pairs of the routing devices providing connecting nodes define segments (or path portions) of the

topology between a source and a destination and, in various embodiments of the present invention, at least one of the network appliances **400** is coupled between each of the pairs of connected routing devices to monitor communications therebetween. However, for purposes of the present invention, a connecting node may include a plurality of routing devices without network appliances **400** positioned between the plurality of routing devices defining a connecting node. In such configurations, the identification of a source of loss of data records will be limited to the resolution of the definition of connecting nodes. In other words, if a plurality of routing devices are grouped together to define a single connecting node for purposes of implementation of the present invention, it will not generally be expected that the individual routing device within such a plurality of devices will be determinable when such a connecting node is determined to be a point of loss for data records.

The routing devices may be routers which track data packets by both level 3 (such as IP) and/or possibly level 2 address information. However, the routing devices may alternatively be bridges and/or switch devices which do not track routed communication packets based on an IP address so long as such devices are able to provide counts filtered based upon source and destination device as will be described herein. An illustrative embodiment of the present invention including network appliance such as the network appliance **400** between each connecting node routing device is further illustrated in **Figure 5** as will be described further herein.

As shown for the embodiments of **Figure 4**, the network appliance **400** includes a transceiver **415** configured to communicate with the service quality management station **410** and further to monitor communications from the network device **412** so as to obtain a count of a number of data records flowing to or from the network device **412**. The illustrated network appliance **400** in **Figure 4** further includes a timer **420**, a filter circuit **425** and a counter circuit **430**. The filter circuit (or filter) **425** identifies ones of a plurality of data records which are detected by the network appliance **400** that are being transmitted from a source device to a destination device on the IP network **405** to provide data record counts specific to a particular source to destination data flow. The counter circuit (counter) **430** counts the filtered data records detected by the filter circuit **425**. Furthermore, the timer **420** provides

timing information to the counter circuit **430** which may be used to reset the counter circuit **430** to define a determined time window over which data records will be counted. Obtained counts from the counter circuit **430** may then be provided to the service quality management station **410** by the transceiver (transmitter/receiver) **415**.

- 5 The counts may be provided, for example, to the receiver circuit **355** illustrated in **Figure 3**.

Referring now to **Figure 5**, an exemplary network topology between a source **SRC** and a destination **DEST** will be described. The network topology includes 7 connecting nodes defined by the routers **R1-R7**. The network topology further
10 includes a total of 14 network appliances **A1-A14**. Pairs of adjacent routers define segments or path sections of the topology between the source **SRC** and the destination **DEST**. One of the network appliances **A1-A14** is coupled between each pair of routers and/or source/destination devices. For example, a network appliance **A1** is coupled between the source **SRC** and the router **R1**. The network appliance **A2** is
15 connected between the router **R1** and the router **R2** and so on. As used herein, the term "coupled between" includes logically coupled, such as in embodiments in which the network appliances are, for example, implemented on the routing devices defining the nodes, as well as physically coupled, as in embodiments where the network appliances are distinct physical devices physically positioned between routing devices
20 on the network. The network appliances **A1-A14** are configured to monitor data transmitted on the network segment to which they are connected. In various embodiments of the present invention the network appliances **A1-A14** collect data record information such as numbers of packets transmitted, numbers of packets received and numbers of packets dropped. Information may be collected by the
25 network appliances **A1-A14** in specified time window buckets, such as one minute buckets.

It is to be understood that other source **SRC** and destination **DEST** devices may be coupled to the communications network which similarly transmit data packets through various of the routers **R1-R7** which communication flows may also be
30 monitored by the network appliances **A1-A14**. Accordingly, in various embodiments of the present invention, the network appliances **A1-A14** are configured to collect data

for specific flows, such as data being transmitted from a specific source **SRC** to a specific destination **DEST**. The routers **R1-R7** are typically configured to route data from an incoming segment of the communication network to an appropriate outgoing segment based upon routing information maintained by the respective routers **R1-R7**. Such routing information is typically maintained in a table called a routing table.

For purposes of the description of operations for various embodiments of the present invention herein, utilizing the illustrated topology of **Figure 5**, it is to be understood that the illustrated topology information identifies all possible paths between the source **SRC** and destination **DEST** and the relationship between routers and network appliances on those paths. It is also to be understood that, in various embodiments, the count information from the network appliances may be provided from current counters or, alternatively, from stored prior period counts. It is further to be understood that means may be provided for synchronizing the time reference of the network appliances **A1-A14** to facilitate monitoring of comparable data flows over the communications network. In various embodiments, the routers **R1-R7** will typically further be configured to provide information, such as interface statistics and routing table information, to a service quality management station **150, 410**. The examples provided herein with reference to the topology shown in **Figure 5** will further assume that the various paths between the source **SRC** and the destination **DEST** do not allow loop data flows (*i.e.*, data record flow will all be downstream wherein the source **SRC** is the upstream reference and the destination **DEST** is the downstream reference.) However, it is to be understood that the present invention may be utilized with complex routings so long as upstream is understood to refer to the source **SRC** side and downstream is understood to refer to the destination **DEST** side for data record flow counting along each segment so as to allow a determination of expected input and/or output data flows at various network appliances **A1-A14** included in the network topology.

Referring now to **Figures 6 and 7**, operations related to determining a point of loss for data records to be communicated between a source **SRC** and a destination **DEST** on a communication network will now be further described for various

embodiments of the present invention. As shown in the embodiments illustrated in **Figure 6**, operations begin at block **700** with determination of the topology of the communication network between the source **SRC** and the destination **DEST** including the plurality of connecting nodes therebetween. A number of data records from the source **SRC** directed to the destination **DEST** passing between respective ones of the connecting nodes is monitored during a determined period of time (block **705**). Such monitoring may include the service quality management station **125, 410** identifying one or more of the network appliances **A1-A14** on the topology between the source **SRC** and the destination **DEST** and obtaining the number of data records from the source **SRC** directly to the destination **DEST** during the determined time period from the respective one or more network appliances **A1-A14**. If a problem is encountered in the network causing data records to be lost during transmission between the source **SRC** and the destination **DEST**, one or more of the connecting nodes **R1-R7** is identified as the point of loss based on the monitored number of data records provided by the network appliances **A1-A14** and the determined topology of the communications network. The identification of the point of loss may generally be understood as isolating a connecting node **R1-R7** for which the inflows of data between the source **SRC** and the destination **DEST** does not correspond to the outflow of data from the source **SRC** to the destination **DEST** as will be more fully described with respect to particular examples herein.

Operations will now be described further with reference to the embodiments illustrated in **Figure 7** beginning with identification of at least one first hop one of the network appliances which is coupled to the source over the communication network (block **800**). For example, referring to **Figure 5**, the network appliance **A1** defines a first hop one of the network appliances **A1-A14** with reference to the source **SRC**. Adjacent (or next hop) ones of the network appliances coupled between the first hop one of the network appliances and the destination **DEST** are identified (block **805**). For example, referring to **Figure 5**, network appliances **A2** and **A3** are located downstream of the first hop network appliance **A1** between network appliance **A1** and the destination **DEST**.

The generation of counts of a number of data records passing between the source **SRC** and the destination **DEST** at various hops or steps along the network topology as described herein is measured over a finite time period which is determined for purposes of the analysis. In one optional aspect of the illustrated
5 embodiments of **Figure 8**, the determined period of time for counting data records is defined for respective hops in the network topology progressively further downstream from the source **SRC** based on a delay between the respective ones of the network appliances **A1-A14** in the path between the source **SRC** and the destination **DEST** rather than utilizing a fixed time period for each based on reference to a time
10 synchronization reference point. The delay may be determined based on a network model, assumptions, or information obtained from the routing devices and/or network appliances. The time period shift between respective ones of the network appliances along the path between the source **SRC** and the destination **DEST** may, for example, be based on an average delay between respective ones of the network appliances
15 which average delay, in turn, may be determined over a specified averaging window or time period. Alternatively, a fixed time period without relative start and stop time shifts may be utilized by otherwise accounting for differences in arrival time of specific data records. For example, analysis operations to identify the source of loss of data packets as described herein could be executed during a period of substantially
20 uniform transmission of data records between the source **SRC** and the destination **DEST** to provide consistent rate measurements at various stages in the path. Where a variable time delay is applied for defining different start times for the determined period of time for obtaining counts of data records, the counts could be individually referenced between the first hop network appliance **A1** and each downstream
25 respective device. Alternatively, an expected average delay per hop could be utilized and multiplied for respective ones of the downstream network appliances based upon the number of hops displaced in the network location each network appliance is from the source **SRC**.

As shown in the embodiment of **Figure 5**, the first hop one of the network
30 appliances **A1** is coupled to the source **SRC** without intervening ones of the network appliances being coupled between the source **SRC** and the first hop one of the

network appliances **A1**. Furthermore, the next hop ones of the network appliances **A2, A3** are coupled between the first hop network appliance **A1** and the destination **DEST** without intervening ones of the network appliances being coupled therebetween.

5 A count of the number of data records from the source directed to the destination obtained by the first node network appliances **A1, A2, A3** during the determined time period is obtained by the service quality management station **125, 410** (block **815**). As shown in the illustration of **Figure 8**, these obtained counts of numbers of data records may, optionally, be adjusted to compensate for in transit
10 introduced changes to data records (block **820**). For example, the obtained numbers of data records may be adjusted to compensate for encryption related changes in data records introduced by a connecting node coupled between successive ones of the network appliances. With reference to **Figure 5**, for example, if encryption was introduced by the router **R1** which increased the volume of data by a known factor,
15 the data record number counts from the network appliance **A1** could be adjusted upward accordingly or the numbers from network appliances **A2** and **A3** could be adjusted downwardly accordingly to remove the effects of encryption overhead from the analysis of conservation of flow of the data records.

 A threshold amount for use in comparing input and output data flows with
20 reference to a connecting node, such as the routing device **R1**, may be established (block **825**). For example, the threshold amount defining an allowable inequality between input flows and output flows for a connecting routing device may be established based on an expected timing related variability between numbers of data records obtained by respective ones of the network appliances **A1-A14**. The threshold
25 amount could further be established based on a percentage of data record throughput for respective ones of the network appliances **A1-A14**. However, it is also to be understood that a default value of zero (*i.e.*, the number of data records in is required to equal the number of data records out for purposes of comparison) or higher could be established in advance and not further adjusted.

30 The number of data records from the source **SRC** directed to the destination **DEST** obtained by a first hop one of the network appliances (such as **A1**) is then

compared with the number of data records from the source **SRC** directed to the destination **DEST** obtained by ones of the next hop network appliances coupled between the first hop network appliance and the destination (such as network appliances **A2** and **A3**) (block **830**). The results of the comparison may be used to
5 determine if the counts obtained from the first hop network appliance (such as **A1**) differ by the threshold amount or more from the number of data records from the source **SRC** directed to the destination **DEST** obtained by the next hop network appliances (such as network appliances **A2**, **A3**).

If a difference exceeding the threshold amount is identified (block **835**), then
10 the intervening connecting node (such as **R1**) is identified as a point of loss for data records. In a typical communication network environment, path joiner may cause data outflows from a routing device to be greater than data inflows from an individual upstream device. Accordingly, the described threshold amounts and comparison should be understood as specifying detection of outflows less than inflows, not greater
15 than inflows, by the threshold amount.

As shown in **Figure 8**, operations may cease on detection of a point of loss (block **835**). However, in alternative embodiments of the present invention where it is desirable to determine if there are a plurality of connecting nodes which are a point of loss for data records, operations continue even after a point of loss connecting node is
20 identified to identify any additional points of loss. If the data records from the input and output side network appliances (such as **A1**, **A2** and **A3**) for a connecting node do not differ by an amount exceeding the threshold amount, the respective connecting node (such as **R1**) is not identified as a point of loss (block **835**). It is then determined if operations have already been processed through all hops to the destination **DEST**
25 (such as completing counts for network appliance **A1-A14** thus, checking all the connecting node routing devices **R1-R7** between the source **SRC** and the destination **DEST**) (block **840**). If not, operations return to block **830** and proceed as described previously. Operations would similarly proceed back to block **830** regardless of early identification of a point of loss connecting node if it is desired to characterize
30 performance of the entire path.

While operations have been described with reference to hop by hop count comparisons flowing from the upstream source **SRC** through the downstream destination **DEST** location, operations need not proceed in such a manner, but, instead, may proceed in any desired order so long as data is collected for comparison which identifies each of the input and output paths for data records passing between the source **SRC** and destination **DEST** for each respective connecting node routing device to be analyzed. Furthermore, the order of analysis need not be connected with the order of obtaining the data record counts for analysis from the respective network appliances **A1-A14**. Such data may be gathered in whatever order or sequence is most convenient for the service quality management station **125, 410** and may further be collected in response to a triggering event such as a user request, a detected network performance degradation or identified problem, or a routine time scheduled initiation of an analysis. The data comparison once the records are obtained from the respective network appliances **A1-A14** may proceed in a variety of known sequences at the service quality management station **125, 410** including either sequential or parallel processing as will be understood by those of skill in the art. Accordingly, terminology related to first hop and next hop ones of the network appliances **A1-A14** and upstream and downstream directions merely refers to the tracking of incoming and outgoing data flows respectively for comparison at ones of the connecting nodes.

To further facilitate understanding of operations according to various embodiments of the present invention, an example will now be provided based on the network topology illustrated in **Figure 5** and the data record traffic count going through the network during a determined period of time as defined by Table 1 below. Table 1 indicates flows for respective hops expressed in average bits per second for 3 determined time frames **T1, T2** and **T3** as shown by the respective columns. The numerical values shown in parenthesis in Table 1 under Columns **T1** and **T3** indicate average bits per second which should have been identified at respective ones of the network appliances if the network was functioning properly. As indicated by the **A1-A14** reference in the "Network Appliance" column of Table 1, the rows show the counts obtained from the respective ones of the network appliances **A1-A14** as shown in **Figure 5**.

Table 1

Network Appliance	T1	T2	T3
A1 (S->R1)	1000	1000	1000
A2(R1->R2)	700	1000	600
A3 (R1->R3)	0	0	0
A4 (R2->R4)	400	1000	300
A5 (R3->R4)	0	0	0
A6 (R1->R4)	300	0	400
A7 (R4->R5)	0	0	0
A8 (R4->R6)	0	0	400
A9 (R4->R7)	700	1000	300
A10 (R5->R7)	100(300)	0	50(300)
A11 (R6->R7)	0	0	400
A12 (R7->D)	800(1000)	1000	750(1000)
A13 (R2->R5)	300	0	300
A14 (R3->R6)	0	0	0

As will now be described further with respect to analysis of the data shown in Table 1 according to embodiments of the present invention, operations essentially utilize the current traffic information as provided in Table 1 from a network appliance at a first hop (or displacement) from the source **SRC** and compare the data with accumulated traffic information gathered from each of the next hop (downstream adjacent) network appliances. If the respective values compare favorably, for example, within a defined error range allowed by the threshold amount, then operations continue with additional ones of the path segments for which data records are detected as being passed on their way to the destination. Path searching as described with reference to **Figure 7** may cease once a problem is identified or continue until completed in case there are more than one problem devices in the network. In addition, input and output data flows may be maintained for each router **R1-R7** during analysis which may be utilized for verification purposes to confirm that all data was properly handled.

Referring again to the circumstances indicated by the data in column T1 of Table 1, 1000 bits per second of data records are detected as leaving from the source **SRC** addressed to the destination **DEST** while only 800 bits per second are detected as arriving at the destination **DEST**. While count values are expressed, for purposes of this example, as normalized to a bits per second form, the analysis could similarly be applied using total bit counts over a defined window. For purposes of this example, the data obtained, as indicated in Table 1, for time period T1 will be analyzed on a hop by hop basis, starting with the upstream network appliance **A1** located closest to the source **SRC**. This first step analysis is illustrated in Table 2 below:

Table 2

Appliance Path	Rate	Router	Next Appliance	Next Rate	Notes
A1	1000	R1			
			A2	700	New Path
			A6	300	New Path
			A3	0	
				1000	Total, no loss

As shown in Table 2, the source **SRC** is detected as sending 1000 bits per second at network appliance **A1** which passes to router **R1**. The next hop appliances downstream of the router **R1** include network appliances **A2**, **A6** and **A3**. In other words, data from the source **SRC** entering the router **R1** could pass through any one of three alternative paths and be routed successfully to the destination **DEST**. Thus, the respective measured bit per second rate information for each of these next hop appliances is recorded as illustrated in the "Next Rate" column of Table 2 as data is detected between the source **SRC** and the destination **DEST**. The Notes column indicates that 2 new paths are introduced by the output from the router **R1** as a data rate of 0 is shown for network appliance **A3**. The Notes column indicates that the total rate of flows detected at the downstream appliances matches the rate detected at the upstream appliance, indicating no loss of data records at the router **R1**. This conclusion with respect to the first connecting node router **R1** is shown in the router summary Table 3 below:

Table 3

Router	Input	Output	Notes
R1	1000	1000	Added

Comparison operations continue then with reference to each of the respective new paths through network appliance **A2**, shown in Table 4, and network appliance **A6**, shown in Table 5. The information presented in the respective tables may be analyzed as described previously with reference to Table 2. Thus, two new next appliance paths through network appliances **A4** and **A13** are identified in Table 4 and no data loss is indicated for the router **R2**.

Table 4

Appliance Path	Rate	Router	Next Appliance	Next Rate	Notes
A2	700	R2			
			A4	400	New Path
			A13	300	New Path
				700	Total, no loss

Table 5

Appliance Path	Rate	Router	Next Appliance	Next Rate	Notes
A6	300	R4			
			A7	0	
			A9	700	New Path
			A8	0	
				700	Total, extra data, paths joined

Table 5 indicates only one output network appliance **A9** receiving data flows and indicating a new path. It further indicates that the output flows from the router **R4** exceed the input flows which indicates the router **R4** is a path join point as contrasted with a shortfall which would indicate a loss of data packets. The summary information for the respective routers **R2** and **R4** are added to that provided for router **R1** as shown in Table 6.

Table 6

Router	Input	Output	Notes
R1	1000	1000	
R2	700	700	Added
R4	300	700	Added

- The analysis for the next hop based on identified next hop network appliances
- 5 **A4, A13** and **A9** is shown in Tables 7, 8 and 9 respectively. The information contained in these respective tables may be analyzed using the same way as described previously with respect to Tables 2, 4 and 5. Thus, a comparison of the data rates for appliance **A13** and the combined total data rate for next hop appliances **A7** and **A10** indicates a data loss problem with the router **R5** (Table 8). Routers **R4** (Table 7) and
- 10 **R7** (Table 9) show input rates lower than output rates indicating that each is part of a joined path.

Table 7

Appliance Path	Rate	Router	Next Appliance	Next Rate	Note
A4	400	R4			
			A7	0	
			A9	700	Already Processed, Rtr Tbl
			A8	0	
				700	Total, extra data, paths joined

Table 8

Appliance Path	Rate	Router	Next Appliance	Next Rate	Notes
A13	300	R5			
			A7	0	
			A10	100	New Path
				100	Total, Data Loss, Problem R5

15

Table 9

Appliance Path	Rate	Router	Next Appliance	Next Rate	Notes
A9	700	R7			
			A12	800	Done
				800	Total, extra data, paths joined

The results of the analysis of Tables 7-9 are added to the router table, Table 6,
 5 as indicated in Table 10 below:

Table 10

Router	Input	Output	Notes
R1	1000	1000	
R2	700	700	
R4	700	700	Updated
R5	300	100	Added
R7	700	800	Added

Finally, the only identified next network appliance **A10** from Tables 7-9 is
 10 evaluated as shown in Table 11 indicating a path joiner. The results from this step are then added to the router table as illustrated in Table 12:

Table 11

Appliance Path	Rate	Router	Next Appliance	Next Rate	Notes
A10	100	R7			
			A12	800	Done
				800	Total, extra data, paths joined

Table 12

Router	Input	Output	Notes
R1	1000	1000	
R2	700	700	
R4	700	700	
R5	300	100	
R7	800	800	Added

15

Note that, as a result of paths being joined, respective data for various ones of the routers may be updated at each stage. For example, in Table 6, the accumulated total flows for the router **R4** indicated an input of 300 and an output of 700 while, in Table 10, the router **R4** has an indicated input of 700 and an output of 700. The 400 bit per second rate of network appliance **A4**, shown in Table 7, is added to the 300 bits per second rate from network appliance **A6**, shown in Table 5 to provide this result for the router. The information with reference to the router **R7** is similarly updated as shown in Table 12. Thus, information related to knowledge of the network topology is illustrated in **Figure 5**, including knowledge of the respective positions of each of the network appliances **A1-A14**, is used, in addition to the data record count information, to complete the analysis of performance for each of the respective routers **R1-R7**. The evaluation based on these results for each of the respective routers **R1, R2, R4, R5** and **R7** which supported data flows in the example described herein are summarized in Table 13 below:

Table 13

Router	Input	Output	Notes
R1	1000	1000	Good
R2	700	700	Good
R4	700	700	Good
R5	300	100	Data Loss, Interrogate Router for more data
R7	800	800	Good

Thus, it would appear that only the router **R5** was experiencing data loss. Subsequent operations may proceed related to identifying the cause for the data loss at the router **R5**. Various techniques will be understood by those of skill in the art for analyzing a device which has been identified as the root cause for a problem, such as polling for more information from the router to aid in determining the cause. Such polled information could include router statistics, link statistics, such as utilization, drop packets information, error records, etc. Such further analysis is beyond the scope of the present invention and will not be further described herein.

The flowcharts and block diagrams of **Figures 1** through **7** illustrate the architecture, functionality, and operation of possible implementations providing for

determining a point of loss for data records on a communication network according to various embodiments of the present invention. In this regard, each block in the flow charts or block diagrams represents a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the blocks may occur out of the order noted in the figures. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. Furthermore, in certain embodiments of the present invention, such as object oriented programming embodiments, the sequential nature of the flowcharts may be replaced with an object model such that operations and/or functions may be performed in parallel or sequentially.

Furthermore, fewer or more functions may be provided as well as functions which are identified as separate functions may be combined while still coming within the teachings of the present invention. For example, the topology detection circuit **350** is shown as a single application, however, this application could be two or more applications. Similarly, the topology detection circuit **350**, the receive circuit **355** and the comparison circuit **330** may be combined in a single application. Thus, the present invention should not be construed as limited to the specific configurations illustrated but is intended to cover all configurations which may carry out the operations described herein.

In the drawings and specification, there have been disclosed typical preferred embodiments of the invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

THAT WHICH IS CLAIMED:

1. A method for determining a point of loss for data records to be communicated between a source and a destination on a communication network, the method comprising the steps of:

5 determining a topology of the communication network between the source and the destination, the topology including a plurality of connecting nodes;

monitoring a number of data records from the source directed to the destination passing between ones of the connecting nodes during a determined period of time; and

10 identifying at least one of the connecting nodes as the point of loss based on the monitored number of data records and the determined topology.

2. The method of Claim 1 wherein a plurality of network appliances configured to obtain a number of data records passing between a pair of connecting nodes during a time period are positioned between respective ones of the connecting nodes, and wherein the monitoring step further comprises the steps of:

15 identifying at least one of the network appliances on the topology; and

obtaining the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time.

20

3. The method of Claim 2 wherein the steps of identifying at least one of the network appliances on the topology and obtaining the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time further comprise the steps of:

25 identifying at least one first hop one of the network appliances which is coupled to the source over the communication network;

identifying at least one next hop one of the network appliances which is coupled between the at least one first hop one of the network appliances and the destination;

obtaining a number of data records from the source directed to the destination obtained by the at least one first hop one of the network appliances and the at least one next hop one of the network appliances during the determined time period; and

wherein the step of identifying at least one of the connecting nodes as the
5 point of loss further comprises the steps of:

comparing the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between
10 the one of the at least one first hop one of the network appliances and the destination; and

identifying a connecting node positioned between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances as the point of loss for data records if the number of data records from the
15 source directed to the destination obtained by one of the at least one first hop one of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination.

20

4. The method of Claim 3 wherein the at least one first hop one of the network appliances is coupled to the source without intervening ones of the network appliances being coupled between the source and the first hop one of the network appliances and wherein the at least one next hop one of the network appliances is
25 coupled between the at least one first hop one of the network appliances and the destination without intervening ones of the network appliances being coupled between the at least one first hop one of the network appliances and the at least one next hop one of the network appliances.

30 5. The method of Claim 3 wherein the step of comparing the number of data records from the source directed to the destination obtained by one of the at least

one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination further comprises the step of comparing a
5 number of data records from the source directed to the destination obtained by an upstream one of the network appliances with a number of data records from the source directed to the destination obtained by at least one downstream one of the network appliances coupled between the upstream one of the network appliances and the destination at an adjacent downstream position for successive ones of the network
10 appliances until at least one of the destination is reached or at least one of the connecting nodes is identified as the point of loss for data records and wherein the step of identifying a connecting node positioned between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances as the point of loss for data records comprises the step of identifying a
15 connecting node positioned between the upstream one of the network appliances and corresponding downstream ones of the network appliances as the point of loss for data records if the number of data records from the source directed to the destination obtained by the upstream one of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained
20 by the corresponding downstream ones of the network appliances.

6. The method of Claim 5 wherein the step of comparing a number of data records from the source directed to the destination obtained by an upstream one of the network appliances with a number of data records from the source directed to
25 the destination obtained by at least one downstream one of the network appliances coupled between the upstream one of the network appliances and the destination at an adjacent downstream position is repeated for successive ones of the network appliances on the topology until the destination is reached and wherein the step of identifying at least one of the connecting nodes as the point of loss further comprises
30 the step of identifying all connecting nodes positioned between upstream ones of the network appliances and corresponding downstream ones of the network appliances as

points of loss for data records if the number of data records from the source directed to the destination obtained by respective upstream ones of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by corresponding downstream ones of the network appliances.

7. The method of Claim 3 further comprising the step of adjusting obtained numbers of data records from the source directed to the destination to compensate for in transit introduced changes to data records before comparing the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination.

8. The method of Claim 7 wherein the step of adjusting obtained numbers of data records comprises the step of adjusting obtained numbers of data records from the source directed to the destination to compensate for encryption related changes in data records introduced by a connecting node coupled between the a first hop one and at least one next hop one of the network appliances.

9. The method of Claim 3 further comprising the step of defining the determined period of time for the at least one first hop one of the network appliances and the at least next hop one of the network appliances based on a delay between the at least one first hop one of the network appliances and the at least next hop one of the network appliances.

10. The method of Claim 9 wherein the step of defining the determined time period further comprises the step of defining the determined period of time for the at least one first hop one of the network appliances and the at least next hop one of the network appliances based on an average delay between the at least one first hop

one of the network appliances and the at least next hop one of the network appliances determined over an averaging window.

11. The method of Claim 3 further comprising the step of defining the
5 threshold amount based on an expected timing related variability between numbers of data records obtained by ones of the network appliances.

12. The method of Claim 11 wherein the step of defining the threshold
amount further comprises the step of defining the threshold amount based on a
10 percentage of data record throughput for respective ones of the network appliances.

13. The method of Claim 3 wherein the connecting nodes are routing
devices selected from the group consisting of routers, bridges and switches.

14. The method of Claim 3 wherein a network appliance is positioned
15 between each defined connecting node in the topology and all other adjacent defined connecting nodes in the topology.

15. The method of Claim 14 wherein at least one of the defined connecting
20 nodes comprises a plurality of routing devices.

16. A system for determining a point of loss for data records to be
communicated between a source and a destination on a communication network, the
system comprising:

25 a memory including a topology of the communication network between the source and the destination, the topology including a plurality of connecting nodes;

a receiver that receives from a plurality of network appliances at determined
locations on the communication network a number of data records from the source
directed to the destination passing between ones of the connecting nodes during a
30 determined period of time; and

a comparison circuit that identifies at least one of the connecting nodes as the

point of loss based on the received number of data records, the locations of the network appliances and the topology.

17. The system of Claim 16 further comprising the plurality of network
5 appliances wherein pairs of the connecting nodes define segments of the topology between the source and the destination and wherein at least one of the network appliances is coupled between each of the pairs of the connecting nodes.

18. The system of Claim 17 wherein at least one of the network appliances
10 further comprises:

a timer;

a filter that identifies ones of a plurality of data records detected by the at least one of the network appliances that are being transmitted from the source to the destination on the communications network;

15 a counter that counts filtered one of the plurality of data records, the counter being configured to be reset responsive to the timer; and

a transmitter that transmits counts from the counter to the receiver.

19. The system of Claim 17 wherein the filter is configured to identify
20 ones of the plurality of data records based on the source Internet Protocol (IP) address and destination IP address of a data packet containing data records detected by the at least one of the network appliances.

20. A system for determining a point of loss for data records to be
25 communicated between a source and a destination on a communication network, the system comprising:

means for determining a topology of the communication network between the source and the destination, the topology including a plurality of connecting nodes;

30 means for monitoring a number of data records from the source directed to the destination passing between ones of the connecting nodes during a determined period of time; and

means for identifying at least one of the connecting nodes as the point of loss based on the monitored number of data records and the determined topology.

21. The system of Claim 1 further comprising:

5 a plurality of network appliances configured to obtain a number of data records passing between a pair of connecting nodes during a time period, ones of the network appliances being positioned between respective ones of the connecting nodes; wherein the means for monitoring further comprises:
means for identifying at least one of the network appliances on the topology;
10 and

means for obtaining the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time.

15 22. The system of Claim 21 wherein the means for identifying at least one of the network appliances on the topology and the means for obtaining the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time further comprise:

means for identifying at least one first hop one of the network appliances
20 which is coupled to the source over the communication network;

means for identifying at least one next hop one of the network appliances which is coupled between the at least one first hop one of the network appliances and the destination;

means for obtaining a number of data records from the source directed to the
25 destination obtained by the at least one first hop one of the network appliances and the at least one next hop one of the network appliances during the determined time period;
and

wherein the means for identifying at least one of the connecting nodes as the point of loss further comprises:

30 means for comparing the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network

appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination; and

5 means for identifying a connecting node positioned between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances as the point of loss for data records if the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances differs by a threshold amount from the number
10 of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination.

23. The system of Claim 22 wherein the at least one first hop one of the
15 network appliances is coupled to the source without intervening ones of the network appliances being coupled between the source and the first hop one of the network appliances and wherein the at least one next hop one of the network appliances is coupled between the at least one first hop one of the network appliances and the destination without intervening ones of the network appliances being coupled between
20 the at least one first hop one of the network appliances and the at least one next hop one of the network appliances.

24. The system of Claim 22 wherein the means for comparing the number of data records from the source directed to the destination obtained by one of the at
25 least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination further comprises means for comparing a number of data records from the source directed to the destination obtained by an
30 upstream one of the network appliances with a number of data records from the source directed to the destination obtained by at least one downstream one of the network

appliances coupled between the upstream one of the network appliances and the destination at an adjacent downstream position for successive ones of the network appliances until at least one of the destination is reached or at least one of the connecting nodes is identified as the point of loss for data records and wherein the means for identifying a connecting node positioned between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances as the point of loss for data records comprises means for identifying a connecting node positioned between the upstream one of the network appliances and corresponding downstream ones of the network appliances as the point of loss for data records if the number of data records from the source directed to the destination obtained by the upstream one of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by the corresponding downstream ones of the network appliances.

15

25. The system of Claim 24 wherein the means for comparing a number of data records from the source directed to the destination obtained by an upstream one of the network appliances with a number of data records from the source directed to the destination obtained by at least one downstream one of the network appliances coupled between the upstream one of the network appliances and the destination at an adjacent downstream position is configured to compare successive ones of the network appliances on the topology until the destination is reached and wherein the means for identifying at least one of the connecting nodes as the point of loss further comprises means for identifying all connecting nodes positioned between upstream ones of the network appliances and corresponding downstream ones of the network appliances as points of loss for data records if the number of data records from the source directed to the destination obtained by respective upstream ones of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by corresponding downstream ones of the network appliances.

30

26 The system of Claim 22 further comprising means for adjusting
obtained numbers of data records from the source directed to the destination to
compensate for in transit introduced changes to data records before comparing the
number of data records from the source directed to the destination obtained by one of
5 the at least one first hop one of the network appliances with the number of data
records from the source directed to the destination obtained by ones of the at least one
next hop one of the network appliances coupled between the one of the at least one
first hop one of the network appliances and the destination.

10 27. The system of Claim 26 wherein the means for adjusting obtained
numbers of data records comprises means for adjusting obtained numbers of data
records from the source directed to the destination to compensate for encryption
related changes in data records introduced by a connecting node coupled between the
a first hop one and at least one next hop one of the network appliances.

15 28. The system of Claim 22 further comprising means for defining the
determined period of time for the at least one first hop one of the network appliances
and the at least next hop one of the network appliances based on a delay between the
at least one first hop one of the network appliances and the at least next hop one of the
20 network appliances.

25 29. The system of Claim 28 wherein the means for defining the determined
time period further comprises means for defining the determined period of time for
the at least one first hop one of the network appliances and the at least next hop one of
the network appliances based on an average delay between the at least one first hop
one of the network appliances and the at least next hop one of the network appliances
determined over an averaging window.

30 30. The system of Claim 22 further comprising means for defining the
threshold amount based on an expected timing related variability between numbers of
data records obtained by ones of the network appliances.

31. The system of Claim 30 wherein the means for defining the threshold amount further comprises means for defining the threshold amount based on a percentage of data record throughput for respective ones of the network appliances.

5

32. The system of Claim 22 wherein the connecting nodes are routing devices selected from the group consisting of routers, bridges and switches.

33. The system of Claim 22 wherein a network appliance is positioned between each defined connecting node in the topology and all other adjacent defined connecting nodes in the topology.

10

34. The system of Claim 33 wherein at least one of the defined connecting nodes comprises a plurality of routing devices.

15

35. A computer program product for determining a point of loss for data records to be communicated between a source and a destination on a communication network based on a topology of the communication network between the source and the destination, the topology including a plurality of connecting nodes, the computer program product comprising:

20

a computer-readable storage medium having computer-readable program code embodied in said medium, said computer-readable program code comprising:

computer-readable program code which monitors a number of data records from the source directed to the destination passing between ones of the connecting nodes during a determined period of time; and

25

computer-readable program code which identifies at least one of the connecting nodes as the point of loss based on the monitored number of data records and the determined topology.

30

36. The computer program product of Claim 35 wherein a plurality of network appliances configured to obtain a number of data records passing between a

pair of connecting nodes during a time period are positioned between respective ones of the connecting nodes, wherein the computer-readable program code which monitors further comprises:

5 computer-readable program code which identifies at least one of the network appliances on the topology; and

computer-readable program code which obtains the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time.

10 37. The computer program product of Claim 36 wherein the computer-readable program code which identifies at least one of the network appliances on the topology and the computer-readable program code which obtains the number of data records from the source directed to the destination obtained by the identified at least one network appliance during the determined period of time further comprise:

15 computer-readable program code which identifies at least one first hop one of the network appliances which is coupled to the source over the communication network;

20 computer-readable program code which identifies at least one next hop one of the network appliances which is coupled between the at least one first hop one of the network appliances and the destination;

computer-readable program code which obtains a number of data records from the source directed to the destination obtained by the at least one first hop one of the network appliances and the at least one next hop one of the network appliances during the determined time period; and

25 wherein the computer-readable program code which identifies at least one of the connecting nodes as the point of loss further comprises:

30 computer-readable program code which compares the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the

network appliances and the destination; and

computer-readable program code which identifies a connecting node positioned between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances as the point of loss for data records if the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination.

38. The computer program product of Claim 37 wherein the at least one first hop one of the network appliances is coupled to the source without intervening ones of the network appliances being coupled between the source and the first hop one of the network appliances and wherein the at least one next hop one of the network appliances is coupled between the at least one first hop one of the network appliances and the destination without intervening ones of the network appliances being coupled between the at least one first hop one of the network appliances and the at least one next hop one of the network appliances.

39. The computer program product of Claim 37 wherein the computer-readable program code which compares the number of data records from the source directed to the destination obtained by one of the at least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination further comprises computer-readable program code which compares a number of data records from the source directed to the destination obtained by an upstream one of the network appliances with a number of data records from the source directed to the destination obtained by at least one downstream one of the network appliances coupled between the upstream one of the network appliances

and the destination at an adjacent downstream position for successive ones of the network appliances until at least one of the destination is reached or at least one of the connecting nodes is identified as the point of loss for data records and wherein the computer-readable program code which identifies a connecting node positioned
5 between the at least one first hop one of the network appliances and the ones of the at least one next hop one of the network appliances as the point of loss for data records comprises computer-readable program code which identifies a connecting node positioned between the upstream one of the network appliances and corresponding downstream ones of the network appliances as the point of loss for data records if the
10 number of data records from the source directed to the destination obtained by the upstream one of the network appliances differs by a threshold amount from the number of data records from the source directed to the destination obtained by the corresponding downstream ones of the network appliances.

40. The computer program product of Claim 39 wherein the computer-readable program code which compares a number of data records from the source directed to the destination obtained by an upstream one of the network appliances with a number of data records from the source directed to the destination obtained by
15 at least one downstream one of the network appliances coupled between the upstream one of the network appliances and the destination at an adjacent downstream position compares successive ones of the network appliances on the topology until the destination is reached and wherein the computer-readable program code which identifies at least one of the connecting nodes as the point of loss further comprises
20 computer-readable program code which identifies all connecting nodes positioned between upstream ones of the network appliances and corresponding downstream ones of the network appliances as points of loss for data records if the number of data records from the source directed to the destination obtained by respective upstream ones of the network appliances differs by a threshold amount from the number of data
25 records from the source directed to the destination obtained by corresponding downstream ones of the network appliances.

41. The computer program product of Claim 37 further comprising computer-readable program code which adjusts obtained numbers of data records from the source directed to the destination to compensate for in transit introduced changes to data records before comparing the number of data records from the source
5 directed to the destination obtained by one of the at least one first hop one of the network appliances with the number of data records from the source directed to the destination obtained by ones of the at least one next hop one of the network appliances coupled between the one of the at least one first hop one of the network appliances and the destination.

10

42. The computer program product of Claim 41 wherein the computer-readable program code which adjusts obtained numbers of data records comprises computer-readable program code which adjusts obtained numbers of data records from the source directed to the destination to compensate for encryption related
15 changes in data records introduced by a connecting node coupled between the a first hop one and at least one next hop one of the network appliances.

43. The computer program product of Claim 37 further comprising computer-readable program code which defines the determined period of time for the
20 at least one first hop one of the network appliances and the at least next hop one of the network appliances based on a delay between the at least one first hop one of the network appliances and the at least next hop one of the network appliances.

44. The computer program product of Claim 43 wherein the computer-readable program code which defines the determined time period further comprises computer-readable program code which defines the determined period of time for the
25 at least one first hop one of the network appliances and the at least next hop one of the network appliances based on an average delay between the at least one first hop one of the network appliances and the at least next hop one of the network appliances
30 determined over an averaging window.

45. The computer program product of Claim 37 further comprising computer-readable program code which defines the threshold amount based on an expected timing related variability between numbers of data records obtained by ones of the network appliances.

5

46. The computer program product of Claim 45 wherein the computer-readable program code which defines the threshold amount further comprises computer-readable program code which defines the threshold amount based on a percentage of data record throughput for respective ones of the network appliances.

10

47. The computer program product of Claim 37 wherein the connecting nodes are routing devices selected from the group consisting of routers, bridges and switches.

15

48. The computer program product of Claim 37 wherein a network appliance is positioned between each defined connecting node in the topology and all other adjacent defined connecting nodes in the topology.

20

49. The computer program product of Claim 48 wherein at least one of the defined connecting nodes comprises a plurality of routing devices.

METHODS, SYSTEMS AND COMPUTER PROGRAM PRODUCTS FOR DETERMINING A POINT OF LOSS OF DATA ON A COMMUNICATION NETWORK

Abstract of the Disclosure

Methods, systems and computer program products are provided which may provide for determining a point of loss for data records to be communicated between a source and a destination on a communication network. A topology of the communication network between the source and the destination is determined which includes a plurality of connecting nodes. A number of data records from the source directed to the destination passing between ones of the connecting nodes during a determined period of time is monitored. At least one of the connecting nodes is identified as the point of loss based on the monitored number of data records and the determined topology.

10




Figure 1




Figure 2




Figure 3




Figure 4




Figure 6




Figure 7

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Attorney Docket No. 9209-3

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **METHODS, SYSTEMS AND COMPUTER PROGRAM PRODUCTS FOR DETERMINING A POINT OF LOSS OF DATA ON A COMMUNICATION NETWORK,**

the specification of which

☒ is attached hereto

OR

☐ was filed on _____ as United States Application No. or PCT International Application Number _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or of any PCT International application having a filing date before that of the application on which priority is claimed.

None			<input type="checkbox"/> Yes <input type="checkbox"/> No
Number	Country	MM/DD/YYYY Filed	Priority Claimed
			<input type="checkbox"/> Yes <input type="checkbox"/> No
Number	Country	MM/DD/YYYY Filed	Priority Claimed
			<input type="checkbox"/> Yes <input type="checkbox"/> No
Number	Country	MM/DD/YYYY Filed	Priority Claimed

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

None	
Application Number(s)	Filing Date (MM/DD/YYYY)

Application Number(s)	Filing Date (MM/DD/YYYY)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or § 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application (37 C.F.R. § 1.63(d)).

None		
Appln. Serial No.	Filing Date	Status Patented/Pending/Abandoned

Appln. Serial No.	Filing Date	Status Patented/Pending/Abandoned

Appln. Serial No.	Filing Date	Status Patented/Pending/Abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following registered attorney(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. I also appoint the following registered attorney(s) to represent me before all competent International Authorities in connection with any and all international applications filed by me with an appropriate receiving office claiming priority to the U.S. application. I also appoint the following registered attorney(s) to make or receive payment on my behalf in connection with the filing of such international applications.


Customer Number 20792

Send correspondence to: Needham J. Boddie
Myers Bigel Sibley & Sajovec
Post Office Box 37428
Raleigh, NC 27627

Direct telephone calls to: Robert W. Glatz
(919) 854-1400

Facsimile: (919) 854-1401

Full name of (first/sole) inventor: Kenneth Lee Harper

Inventor's
Signature:  Date: 8/16/00

Residence: Coral Springs, Florida

Citizenship: United States of America

Post Office Address: 7011 NW 39th Court
Coral Spring, Florida 33065